





## DIMENSIONI/Measures

<b>VOLUME CON IMBALLO</b> Volume with packaging	l.1400 x p.1090 x h.580 mm
<b>DIMENSIONI ESTERNE</b> External dimensions	l.1010 x p.1300 x h.420 mm
<b>DIMENSIONI CAMERA</b> Chamber dimensions	l.720 x p.1080 x h.140 mm
<b>PESO NETTO</b> Net weight	140 Kg
<b>PESO LORDO</b> Gross weight	155 Kg
<b>SUPERFICIE TOTALE COTTURA</b> Total cooking surface	0,77 m <sup>2</sup>

## CARATTERISTICHE/Details

<b>BARRIERA TERMICA</b> Thermal barrier	✓
<b>CIELO/PLATEA INDIPENDENTI</b> Ceiling/bedplate controls	✓
<b>ILLUMINAZIONE ALOGENA</b> Halogen lighting	✓
<b>DOPPIO VETRO PANORAMICO FACILMENTE SOSTITUIBILE</b> Easily replaceable panoramic double glass	✓
<b>VALVOLA RILASCIO VAPORE</b> Steam release valve	✓
<b>PORTA BILANCIATA</b> Balanced door	✓
<b>CAMERE SOVRAPPONIBILI</b> Overlapping chambers	✓
<b>PIETRA REFRATTARIA REVERSIBILE</b> Reversible refractory stone	✓

## CAPACITÀ DI COTTURA/Cooking capacity

<b>TEGLIE 600x400</b> 600x400 trays	x2
<b>PIZZA Ø 36</b>	x6
<b>TEMPERATURE</b> Temperatures	50>500 °C

## IMPIANTO ELETTRICO/Electric system

<b>ALIMENTAZIONE</b> Electrical supply	400V 3P+N+T/ 50Hz
	230V 3P+T/ 50Hz
<b>POTENZA</b> Power consumption	9 kW
<b>RESISTENZE e POTENZA</b> Resistors and power consumption	6x - 1500 W
<b>CORRENTE NOMINALE</b> Nominal current	400V 3P+N+T 13 A
	230V 3P+T 22,6 A
<b>CAVO</b> Electric cable	400V 3P+N+T 5G4
	230V 3P+T 5G4